



AN219200CQQ

ENERGY ABSORBING LANYARDS

Fall protection



Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Heavy industry
- Light industry
- Maintenance

Certifications and norms



EN355

Protects against risks



Fall



AN219200CQQ

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Polyester
Length (m)	2
Gate opening (mm)	18
Opening (inch)	0.7074
Lock	Manual system
With connector	yes
Color	Yellow-Black
Connector (user side)	Screw carabiner, steel, opening 18mm
Weight (kg)	2.25
Maximum number of users	1
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



AN219200CQQ

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN219200CQQ	Yellow-Black	2 m	AN219200CQQ	3295249278694	13295249278691	10	1	0.0 kg	60.0 cm	40.0 cm	22.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height