



Fall protection

AN215200CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg



Easy to use

- NFC system guarantees traceability



Durability

- High webbing tenacity thanks to its weave and width



Compatibility

- Compatible with all kind of harnesses

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Heavy industry
- Light industry
- Maintenance

Certifications and norms



EN355
100 KG

Protects against risks



Fall



Fall protection

AN215200CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Grey-Black
Connector (user side)	Screw carabiner, steel, opening 18mm
Benefits element	Comfort
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.6
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



Fall protection

AN215200CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN215200CDD	Grey-Black	2 m	AN215200CDD	3295249277260	0	10	1	16.65 kg	29.0 cm	50.0 cm	40.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height