



Fall protection

PROTECTOR ELEVATOR TR01830U

RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery



Specific benefits



Comfort

- Double swivel for optimum user tracking



Performance

- Double swivel design for optimum user tracking and improved rewinding of the strap in the housing
- Certification above the maximum rated load of 100 kg; product certified at 150 kg



Easy to use

- Automatic carabiners for secure and time-saving locking
- End handle for easy cable winding
- Carrying handle for easy transport

Certifications and norms

EN360

RFU 11.062
150 KG

EN1496

CLASS A
150 KG



UL-AR EN360

AR 1983

Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Protects against risks



Fall



Fall protection

PROTECTOR ELEVATOR TR01830U

RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery

Standards - Details

Technical details

Type of equipment	Cable reel, winch function
Composition of the main support	ABS, Stainless steel
Max. length (m)	30
ARA lenght (m)	30
ARA lenght (inch)	1181.103
Cable diameter (mm)	5
Included elements	Included energy absorber
Color	Black-Orange
Connector (user side)	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Lifespan from manufacturing (years)	20
Weight (kg)	14,5
Maximum load for one person (kg)	150
Fall arrest work situations	Rescue and evacuation, Vertical movement, confined space
Locking system	Inertia locking system
Use of self retracting	Vertical



Fall protection

PROTECTOR ELEVATOR TR01830U

RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TR01830U	Black-Orange	30 m	PROTECTOR ELEVATOR TR01830U	3295249254711	13295249254718	1	1	15.3 kg	47.0 cm	28.0 cm	21.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height