



Hand protection

TERK500 XTREM HEAT

THERMAL SPECIFIC WORKS

Level E cut-resistant reinforced thermal glove, ideal for extreme heat environments



Specific benefits



Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (500°C for 15 seconds)

Applications

- Building
- Finishing works / Craftsmanship
- Light industry
- Maintenance
- Pharmaceutical industry / Laboratories
- Automotive

Certifications and norms



EN 388
2 5 4 4 E



EN 407
4 4 4 2 4 X

Protects against risks



Heat



Cutting



enjoy safety

Edit 05/08/2026
www.deltaplus.eu



Hand protection

TERK500 XTREM HEAT

THERMAL SPECIFIC WORKS

Level E cut-resistant reinforced thermal glove, ideal for extreme heat environments

Standards - Details



EN388:2016+A1:2018

2 [0-4] ABRASION RESISTANCE
5 [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
4 [0-4] PIERCE RESISTANCE
E [A-F] CUT RESISTANCE ISO 13997



EN 407

THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
4 [0-4] CONTACT HEAT RESISTANCE
4 [0-4] CONVECTIVE HEAT
2 [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn textile palm / textile back
Mechanical glove kind	Cut and sewn
Special gloves kind	Welding
Arm level protection	Forearm cuff (< 400mm)
Cuff characteristic	Large safety cuff
Cuff length (mm)	160
Color	Yellow
Size	Unique
Type of packaging	in individual bag

Packaging

Sale unit: in individual bag
36 pairs /box



Safety gloves

TERK500 XTREM HEAT

THERMAL SPECIFIC WORKS

Level E cut-resistant reinforced thermal glove, ideal for extreme heat environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TERK500	Yellow	One size	TERK500 XTREM HEAT	3295249228668	13295249228665	36	1	15.8 kg	50.0 cm	50.0 cm	50.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height